

Thermosetting Rubber Adhesive Fiberglass Tape



G551

IPG4616

3M27

Colour of tapes may look different because they were taken at different environments. All should look the same physically.



Overview

Products G551, IPG4616 and 3M27 are all woven fiberglass cloth coated with a pressure sensitive thermosetting rubber adhesive. While the woven fiberglass cloth substrate may come from the same manufacturers and adhesive coated at respective plants. All these tapes are designed to operate in 600 volt dry applications requiring high mechanical strength and resistance to high temperatures. The woven fiberglass cloth are specially treated and prepared to provide corrosion free protection. The glass cloth will not shrink, rot or burn and has a high tensile strength, is printable and excellent solvent resistance.

Applications

- Insulating electric and induction type furnace power supply leads
- Securing systems requiring high mechanical strength and resistance to high temperatures
- Splicing wire SF and SFF rated 150°C and 180°C
- Insulating motor lead connectors, switcher and controls for furnaces and ovens
- Insulation coli outer wrap
- Provides heat stable insulation for hot spot application
- Bundling heavy gauge wire

Typical Data of Respective Manufacturer

Property	Unit	G551	IPG4616	3M27
Colour	Visual	White	White & Black	White
Adhesive Type	-	Thermosetting Rubber	Thermosetting Rubber	Thermosetting Rubber
Backing Thickness	mm	0.114	0.114	0.125
Adhesive Thickness	mm	0.064	0.064	0.052
Total Thickness	mm	0.178	0.178	0.177
Adhesion Strength	g/cm	551	551	331
Elongation At Break	%	5	3	5
Operating Temperature	°C	150	155	150
Insulation Class	°C	130	155	130
Dielectric Strength	Volt	3,500	2,500	3,000
Electrolytic Corrosion Factor	-	1	1	0.9
Breaking Strength	kg/cm	28.6	33.4	28.6
Continuous Operating Temperature	°C	-18 to 177	-18 to 177	-18 to 177
Specifications	-	CSA, MIL-I-15126-GFT, U.L.	CSA, MIL-T-4053B, U.L., VDE	CSA, U.L.
Roll length	metre	55	55	55
Width	mm	6 to 609	6 to 609	6 to 609
Data provided should not be used to write specifications				
All 3 products are available ex-stock subject to prior sales				

Everjoy Industrial Supplies Pte. Ltd.

38 Woodlands Industrial Park E1, #04-11 Singapore 757700

Telephone: + 65 6748 3093

Fax: +65 6748 7202

Email: admin@everjoy.com.sg